

## **ARMOR 5HP ATF Automatic Transmission Fluid**

ARMOR **ATF 5HP Fluid** is a synthetic ATF (Automatic Transmission Fluid), designed on the basis of high quality hydrocrack oils with a special additive and inhibition, which ensure a perfect function of the automatic transmission. ARMOR ATF 5HP Fluid is an automatic transmission oil ATF of 4/5 stroke automatic transmissions of ZF. ARMOR ATF 5HP Fluid is light brown colored.

**Applications:** A synthetic ATF (Automatic Transmission Fluid) Armor **5HP ATF Transmission Fluid** is primarily designed for 5HP-series (5HP18, 5HP19, 5HP24, 5HP30) automatic transmissions.

Please follow manufacturers' recommendations.

**Specifications:** ARMOR ATF 5HP meets the following performance specifications:

- \* Alfa Romeo 20HP 14891900
- \* ATF LT 71141; ATF LA 2634
- \* BMW 8322 9407765; BMW 8322 9407807
- \* Citroen/ Peugeot AL4 PR 9736.22
- \* Jaguar JLM 20237, Land Rover STC4863
- \* Mercedes A 0019892203
- \* Porsche 999.917.547.00, Renault DP0
- \* Volkswagen/ Audi G 052 162 A1; G 052 162 A2; G 052 162 A6, Volkswagen VW TL 52 162
- \* ZF S671 090 170

### **Product Data Sheet**

**Product Details:**

**Brand Name:** Armor Ultra

**Product Grade:** 5HP

**Product Description:** Automatic Transmission Fluid

### **Typical Product Analysis:**

#	Parameter	Test method	Results
1	Color	VISUAL	Brown
2	Viscosity @ 100°C	ASTM D 445	5.6 cst
3	Viscosity @ 40°C	ASTM D 445	26 cst
4	Viscosity Index	ASTM D 2270	175
5	Density @ 15°C	ASTM D 1298	0.849
6	Pour Point	ASTM D 97	-45°C
7	Flash Point	ASTM D 92	206 °C

